

SPECIFICATIONS (Continued)**4x4, Rear Driveline Angles @ Curb Specifications**

Rear Spring Part No. (5560)	Ride Height At Rear Axle (mm)	En-gine Angle (deg.)	Front U-Joint Angle (deg.)	Rear DS Angle (deg.)	Pinion Angle (deg.)
Regular Cab, 2836 mm Wheelbase, 3.0L Engines, A4LD Transmission, 7.5 In. Axle					
F87A-KA	174	4.75	4.5	8.9	8.6
Regular Cab, 2836 mm Wheelbase, 3.0L Engines, M5OD Transmission, 7.5 In. Axle					
F87A-KA	174	4.75	4.5	8.9	8.6
Regular Cab, 2836 mm Wheelbase, 4.0L Engines, A4LD Transmission, 8.8 In. Axle					
F87A-CB	189	4.75	6.4	10.9	9.1
F87A-KA	174	4.75	5.1	9.5	8.6
Regular Cab, 2836 mm Wheelbase, 4.0L Engines, M5OD Transmission, 8.8 In. Axle					
F87A-CB	189	4.75	3.0	7.4	5.4
F87A-KA	174	4.75	5.1	9.5	8.6
Regular Cab, 2988 mm Wheelbase, 3.0L Engines, A4LD Transmission, 7.5 In. Axle					
F87A-KA	173	4.75	4.0	8.4	5.5
Regular Cab, 2988 mm Wheelbase, 3.0L Engines, M5OD Transmission, 7.5 In. Axle					
F87A-KA	173	4.75	4.0	8.4	5.5
Regular Cab, 2988 mm Wheelbase, 4.0L Engines, A4LD Transmission, 8.8 In. Axle					

(Continued)

4x4, Rear Driveline Angles @ Curb Specifications

Rear Spring Part No. (5560)	Ride Height At Rear Axle (mm)	En-gine Angle (deg.)	Front U-Joint Angle (deg.)	Rear DS Angle (deg.)	Pinion Angle (deg.)
F87A-CB	185	4.75	5.6	10.1	6.0
F87A-KA	173	4.75	4.6	9.0	5.5
Regular Cab, 2988 mm Wheelbase, 4.0L Engines, M5OD Transmission, 8.8 In. Axle					
F87A-CB	185	4.75	5.6	10.1	6.0
F87A-KA	173	4.75	4.6	9.0	5.5
Super Cab, 3197 mm Wheelbase, 3.0L Engines, A4LD Transmission, 7.5 In. Axle					
F87A-KA	165	4.75	2.7	7.1	5.4
Super Cab, 3197 mm Wheelbase, 3.0L Engines, M5OD Transmission, 7.5 in. Axle					
F87A-KA	165	4.75	2.7	7.1	5.4
Super Cab, 3197 mm Wheelbase, 4.0L Engines, A4LD Transmission, 8.8 In. Axle					
F87A-CB	183	4.75	4.3	8.8	5.9
F87A-KA	165	4.75	3.2	7.6	5.4
Super Cab, 3197 mm Wheelbase, 4.0L Engines, M5OD Transmission, 8.8 In. Axle					
F87A-CB	183	4.75	4.3	8.8	5.9
F87A-KA	165	4.75	3.2	7.6	5.4